

Favorit SAE 90 API GL-1



Packages:
20L, 60L, 208L

Meets the requirements and specifications:
SAE 90
API GL-1

[EN] **Favorit SAE 90 API GL-1** A mineral simple-composition gear oil for mild operating conditions (low loads and sliding velocities).

It may be recommended for the lubrication of accessory equipment to be installed in special vehicles (reducers in autocranes, mechanisms on garbage trucks, side lifting components, etc.) when operating at temperatures no lower than 0°C..

[RU] **Favorit SAE 90 API GL-1** минеральное трансмиссионное масло простого состава для мягких условий эксплуатации (невысокие нагрузки и скорости скольжения).

Может быть рекомендовано для смазки вспомогательного оборудования, устанавливаемого на специальные автомобили (редукторы автокранов, агрегатов мусороуборочных машин, узлов подъема борта и т.д.) при эксплуатации при температурах выше 0 °С.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	146,8
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	14,82
Viscosity index	STB 1797	100
Flash point, °C	GOST 4333	241
Pour point, °C	GOST 20287	-15
Density at 20°C, kg/m ³	GOST 3900	887

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.